

SPAULDING MFG., INC.

5366 EAST ROAD SAGINAW, MI 48601 PHONE: 989-777-4550 FAX: 989-777-7430

R.M.V. HOT PATCHER TECHNICAL DATASHEET

TECHNICAL DATA

- 2, 3 & 4 TON CAPACITY
- 105,000 MINIMUM BTU DIESEL OR PROPANE FUEL SOURCE
- AUTOMATIC TEMPERATURE CONTROL
- 12 VOLT BATTERY
- 2 TON - SINGLE AXLE TRAILER WITH ELECTRIC BRAKES AND SAFETY BREAKAWAY
- 3 & 4 TON - TANDEM AXLE TRAILER WITH ELECTRIC BRAKES AND SAFETY BREAKAWAY
- 2, 3 & 4 TON TRAILER FRAME STEEL - RECTANGULAR TUBING
- 8 BOLT WHEELS
- LEAF SPRING AXLES
- HOPPER - FULLY INSULATED
- TRIPLE WALL CONSTRUCTION
- HOPPER FLOOR 1/4" STEEL
- FLOOR, SHOVEL DECK, AND ALL FOUR WALLS ARE HEATED
- 10 GAUGE CAPPING CHANNEL AND CORNER MOLDING ADD STRUCTURAL INTEGRITY TO THE HOPPER PREVENTING IT FROM BECOMING OUT OF SQUARE
- ALL WIRING EXTERNAL TO HOPPER
- PAINT: SANDBLASTED WITH TWO COATS OF EPOXY PRIMER AND URETHANE FINISH
- 2 TON GVWR OF 7,000 LBS.
- 3 & 4 TON GVWR OF 14,000 LBS.
- LENGTH: 14' - 18'
- WIDTH: 88"
- HEIGHT: VARIES BASED ON HOPPER CAPACITY.
- NATM COMPLIANT
- OPERATING CONTROLS LOCATED ON CURBSIDE WHEREVER POSSIBLE
- MANY OPTIONS AVAILABLE



** 2 TON R.M.V HOT PATCHER*



** SHOWN WITH DUMPING HOPPER OPTION*



** SHOWN WITH RECLAIMING OPTION*

5366 EAST ROAD SAGINAW, MI 48601 PHONE: 989-777-4550 FAX: 989-777-7430